

UNI SCALE TERMINAL



UNI NSC S360

DETAILS		Burnett Scale Service	
Harsh Stainless Steel (PTHC)	178 X 159 X 66mm	NEMA 4X IP65	
Operating Temperature	-10 to 45 Degrees C	10 to 95% Humidity	
Power	85 TO 264VAC 47 – 63 Hz . Consumption 12 Watts maximum		
Display	12.7mm Green Vacuum Fluorescent. .		
Performance	* Supports 8 x 350ohm loadcells. 2 or 3m/v jumper selection		
Description	* Simple Scale for Analog loadcells. Identical to the Panther Harsh except it does not have Setpoints and is MUCH Cheaper.		
Mounting	* UNI uses a Universal Mounting bracket that makes Desk or Wall mounting easy.		

FEATURES	BENEFITS
Key Entry	* Keypad used To setup terminal software, to Zero or Tare Scale and enter data for Check Weighing Target weights or printing
COM 1. RS232 Bi Directional	* Interface RS232 Serial devices, Printer, PC, PLC for data input/output
Scale Platform	* Supports all Analog loadcell scales up to 8 x 350ohm loadcells.
20 Weight Updates Per Second	* Quick weight response for accurate weighing in automated systems
Under /Over check Weighing	* UNIs have coloured front panel status lights, when enabled these operate on check weight mode, Accept, Under accept, Over accept or Reject. As well as the lights these limits are available as outputs to control gates, lights etc.
TraxDSP Filtering	* Reduce or eliminate effects of vibration to give a stable weight display. * Provides an ultra quiet Analog front end, propriety hi speed hi resolution A/D and dedicated 16 bit processor for serial processing.
Hazardous Areas	* Panther UNIs use a 5VDC loadcell excitation voltage. They can be used in hazardous area when used with appropriate barriers
Memory	* Stores Target Weights for Check Weighing Feature as well as Zero and Tare references .

CONTACT DETAILS	Burnett Scale Service	PH 0749726224
Barry Whyte	3 Walsh St P.O. Box 1694	Fax 0749727445
	Gladstone Qld 4680	Mobile 0417714842
		Email: burscl@ozemail.com.au