

PANTHER + Plus SCALE TERMINAL



Panther Plus NSC S353

DETAILS		Burnett Scale Service	
Harsh Stainless Steel (PTHK)	178 X 159 X 66mm	NEMA 4X IP65	
Operating Temperature	-10 to 45 Degrees C	10 to 95% Humidity	
Power	85 TO 264VAC 47 – 63 Hz . Consumption 12 Watts maximum		
Display	12.7mm Green Vacuum Fluorescent. .		
Performance	* Supports 8 x 350 ohm loadcells. 2 or 3m/v jumper selection		
Mounting	* Universal Mounting bracket allows easy Desk or Wall Mounting		

OPTIONS:

- * Analog Output Option Card. 0 – 10VDC & 4 – 20Ma

FEATURES	BENEFITS
Numeric Key Entry	* Full Numeric Keypad used To setup terminal software, to Zero or Tare Scale and enter data for Setpoints, Check Weighing Targets or printing
COM 1. RS232 Bi Directional	* Interface RS232 Serial devices, Printer, PC, PLC for data input/output.
Time & Date	* Time & Date feature to enhance printouts
Scale Platform	* Supports all Analog loadcell scales up to 8 x 350ohm loadcells.
20 Weight Updates Per Second	* Quick weight response for accurate weighing in automated systems
Discrete I/O	* 1 Discrete Input and 3 Outputs for dynamic weight Batching
Under /Over check Weighing	* Panther UNIs have coloured front panel status lights, when enabled these operate on check weight mode, Accept, Under accept, Over accept or Reject. As well as the lights these limits are available as outputs to control gates, lights etc.
TraxDSP Filtering	* Reduce or eliminate effects of vibration to give a stable weight display. * Provides an ultra quiet Analog front end, propriety hi speed hi resolution A/D and dedicated 16 bit processor for serial processing.
Hazardous Areas	* Panther UNIs use a 5VDC loadcell excitation voltage. They can be used in hazardous area when used with appropriate barriers
Memory	* Stores Setpoint Target & Preact Weights and Target for Check Weighing Feature as well as Zero, Tare , Time & Date.

CONTACT DETAILS Barry Whyte	Burnett Scale Service 3 Walsh St P.O. Box 1694 Gladstone Qld 4680	PH 0749726224 Fax 0749727445 Mobile 0417714842 Email: burscl@ozemail.com.au
--	--	--